



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C11D 3/02, 17/00		A1	(11) International Publication Number: WO 95/21234
			(43) International Publication Date: 10 August 1995 (10.08.95)
(21) International Application Number: PCT/EP95/00102		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MG, MN, MW, MX, NL, NO, NZ, PL, PT, RO, RU, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ).	
(22) International Filing Date: 11 January 1995 (11.01.95)			
(30) Priority Data: 9402001.3 2 February 1994 (02.02.94) GB			
(71) Applicant (<i>for all designated States except US</i>): CROSFIELD LIMITED [GB/GB]; Bank Quay, Warrington WA5 1AB (GB).		Published <i>With international search report.</i>	
(72) Inventor; and			
(75) Inventor/Applicant (<i>for US only</i>): WEBB, Maurice [GB/GB]; 117 Green Lane, Vicars Cross, Chester, Cheshire CH3 5LD (GB).			
(74) Agent: HUGOT, A., E., P.; Unilever plc, Patent Division, Colworth House, Sharnbrook, Bedford MK44 1LQ (GB).			

(54) Title: MACHINE DISHWASHING COMPOSITIONS

(57) Abstract

A co-granule of a hydrotalcite like material, preferably a Zn/Al or Mg/Al hydrotalcite, and an alkali metal silicate constitutes a good alternative to synthetic hectorites normally used in machine dishwashing compositions.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

MACHINE DISHWASHING COMPOSITIONSFIELD OF THE INVENTION

5

This invention relates to machine dish- and warewashing compositions. These compositions are used for the cleaning of housewares in automatic-dishwashing and warewashing machines and will be referred to in the description as
10 machine dishwashing compositions.

The invention more specifically relates to a substitute to synthetic hectorites for use in machine dishwashing compositions.

15

BACKGROUND OF THE INVENTION

Machine dishwashing compositions usually contain as main components a builder or builder mixture, buffering and/or
20 alkaline agents, a bleaching agent which may be a chlorine or oxygen bleach, and lately also enzymes. Such machine dishwashing compositions are used in the main wash step of machine dishwashing and in general have a satisfactory cleaning performance.

25

It is, however, well known in the dishwashing art that the visual appearance of the cleaned article is a critical factor for a dishwashing composition to be satisfactory to the consumer. Frequently after cleaning of an article a film is formed thereon, which results in the article showing
30 a dull surface when dry, or spots are formed on an article upon drying, both phenomena causing the article to have an "unclean" visual appearance.

35

It is customary to add to the rinsing water a rinse aid composition which causes the articles to dry more evenly and improves the visual appearance of the articles when dry.

5 Although such rinse aid compositions improve said visual appearance in comparison with articles which have not been rinsed with a rinse aid containing rinse liquor, said visual appearance may still need improvement, as, despite the use of a rinse aid, some film- and spot-formation may still occur.

10 It is known from EP-A-0,139,329, EP-A-0,139,331 and EP-A-0,140,435 that the incorporation of an effective level of a layered clay in machine dishwashing compositions reduces the problem of film and spot formation on the washed 15 articles, thereby improving the so-called "glass appearance". EP-A-0139.330 discloses the incorporation of a layered clay in a rinse aid composition.

20 Suitable layered clay minerals according to these art references belong to the geological classes of the smectites, the kaolins, the illites, the chlorites, the attapulgites and the mixed layer clays, which may be either naturally occurring or synthetic, preferably the commercial synthetic hectorites ex Laporte Industries Ltd, known under 25 the tradename Laponite®.

Although the glass appearance benefit of Laponite® clay can indeed be demonstrated synthetic hectorites are expensive products.

30 There is therefore a need for a substitute to synthetic hectorites which, on the one hand will be at least as effective and, on the other hand will constitute an economically interesting alternative.

It is a first goal of the invention to provide a substitute to synthetic hectorites for use in machine dishwashing compositions.

- 5 It is a second goal of the present invention to provide a machine dishwashing composition containing said synthetic hectorites substitute.


Definitions

10

i) Hydrotalcite-like Material

By hydrotalcite-like material, it is understood a product having the following composition:

15



where:

20

M is any 1+ or 2+ cation or combination thereof

N is any 3+ or 4+ cation or combination thereof

k is the sum of the individual mole fractions of the 1+ cations

m is the sum of the individual mole fractions of the 2+ cations

25

n is the sum of the individual mole fractions of the 3+ cations

p is the sum of the individual mole fractions of the 4+ cations

30

where either but not both of k and m or n and p can be zero and $k+m+n+p=1$.

35

A_z^{y-} is any anion of charge $y-$ and mole fraction z, or combination of anions of similar or differing $y-$ and $k+2m+3n+4p-2-zy=0$ and x can range from 1 to 100.




Examples of the cations M in the above formula are Li, Mg²⁺, Zn²⁺, Fe²⁺, Cu²⁺, Sn²⁺, Ca²⁺ and Sr²⁺. Suitable N cations include Al³⁺, Fe³⁺, Ti⁴⁺ and Sn⁴⁺.

Preferred divalent cations are Zn²⁺, Cu²⁺ or Mg²⁺ or a combination of these ions, or a combination with other divalent cations.

The anion A may be an inorganic or organic anion.

Preferred inorganic anions A are Cl⁻, NO₃⁻, SO₄²⁻, CO₃²⁻ and OH⁻. Examples of organic anions are carboxylate ions such as citrate and stearate.

Examples of hydrotalcite-like materials of this invention are:- .



Preparation of hydrotalcite-like compounds is known and has been described in a number of publications including Solid State Ionics 22 (1986) pages 135-141 where there is published a paper by Walter T Reichle entitled "Synthesis of Anionic Clay Minerals (Mixed Metal Hydroxides, Hydrotalcite)" and Chemtech (January 1986) pages 58-63 where there is published a paper by Walter T Reichle entitled "Anionic Clay Minerals".

ii) The Builder Material

Builder materials (phosphates and non-phosphate builder materials) are well-known in the art and many types of organic and inorganic compounds have been described in literature. They are normally used in all sorts of cleaning compositions to provide alkalinity and

buffering capacity, prevent flocculation, maintain ionic strength, extract metals from soils and/or remove alkaline-earth metal ions from washing solutions.

5 The builder material usable herein can be any one or mixture of the various phosphate and preferably non-phosphate builder materials, such as for example the alkalinmetal citrates, carbonates and bicarbonates; nitrilotriacetic acid (NTA); dipicolinic acid (DPA); oxydisuccinic acid (ODS); alkyl- and alkenylsuccinates (AKS); layered silicate; and zeolites. They may be present in the composition of the invention in an amount of from 10% up to about 90% by weight, preferably from 20% to 80% by weight. Particularly preferred builders are citrates, alkenylsuccinates, carbonates, bicarbonates, zeolites, and mixtures thereof.

10

15

iii) The Buffering and/or Alkaline Agent

20 This is normally an alkalinmetal silicate, preferably sodium silicate at a level of from about 1 to about 70% by weight, preferably from 5 to 40% by weight. This material is employed as a cleaning ingredient, source of alkalinity, metal corrosion inhibitor and protector of glaze on china tableware. Typically, silicates with a mol ratio of SiO₂:metal oxide of 0.67 to 4.5 are suitable. Especially effective is sodium silicate having a mol ratio of SiO₂:Na₂O of from about 1.0 to about 3.3., preferably from about 1.8 to about 2.5, normally referred to as sodium disilicate.

25

30

35 NaOH and/or KOH are also commonly used to provide alkalinity in compositions for industrial warewashing machines.

iv) The Bleaching Agent

If present the amount of bleaching agent will preferably lie in a range from 1 to 30% by weight.

5 Alkali metal hypochlorite may be incorporated. Other chlorine bleaches are alkali metal salts of di- and tri-chloro and di- and tri-bromo cyanuric acids.

10 Preferred bleaches are the peroxygen bleaches, such as sodium perborate (tetra- or monohydrate) or sodium percarbonate. These are preferably used in conjunction with a bleach activator which allows the liberation of active oxygen species at a lower temperature. Numerous examples of activators of this type, often also referred to as bleach or peracid precursors, are known in the art. Preferred bleach activators are tetraacetyl ethylene diamine (TAED), glucose pentaacetate (GPA) and the mono-long chain acyl 15 tetraacetyl glucoses as disclosed in WO 91/10719, but other activators such as choline sulphophenylcarbonate (CSPC) as disclosed in US Patents 4,751,015 and 4,818,426 can be used. The amounts of sodium perborate or percarbonate and bleach activator in the compositions preferably do not exceed 20% and 10% by weight respectively, e.g. from 4-20% and from 2-10% by 20 weight respectively.

25 Another peroxygen bleach is potassium monopersulphate. Further peroxygen bleaches which may be used are the organic peroxyacids and their metal salts. Typical peroxy-acids include:

- 30 i) peroxybenzoic acid and ring-substituted peroxybenzoic acids, e.g. peroxy- α -naphthoic acid;
- ii) aliphatic and substituted aliphatic monoperoxy

acids, e.g. peroxylauric acid and peroxystearic acid;

iii) 1, 12-diperoxydodecanedioic acid (DPDA);

iv) 1, 9-diperoxyazelaic acid;

5 v) diperoxybrassylic acid; diperoxysebacic acid and diperoxyisophthalic acid;

vi) 2-decyldiperoxybutane-1,4-dioic acid; and

vii) phthaloylamido peroxycaproic acid (PAP)

10 Instead of or together with said bleach activators, a bleach catalyst, such as the manganese complexes of EP-A-458,397 and the sulphonimines of US Patents 5,041,232 and 5,047,163 may also be added.

15 v) Enzymes

Amylolytic and/or proteolytic enzymes are normally used. The amylolytic enzymes usable herein can be those derived from bacteria or fungi. Preferred amylolytic enzymes are those prepared and described in GB Patent No. 1,296,839, cultivated from the strains of *Bacillus licheniformis* NCIB 8061, NCIB 8059, ATCC 6334, ATCC 6598, ATCC 11945, ATCC 8480 and ATCC 9945 A.

20 Examples of such amylolytic enzymes are those produced and distributed under the Trade-names of SP-95® and Termamyl® by Novo Industri A/S, Copenhagen, Denmark. These amylolytic enzymes are generally presented as granules and may have enzyme activities of from about 2 to 10 Maltose units/milligram. They may be present in the composition of the invention in amounts such that the final composition has amylolytic enzyme activity of 25 from 10³ to 10⁶ Maltose Units/Kilogram.

30 The amylolytic activity as referred to herein can be determined by the method as described by P. Bernfeld

in "Method of Enzymology" Volume I (1955) page 149.

The proteolytic enzymes usable herein are for example
the subtilisins which are obtained from particular
5 strains of *B. Subtilis* and *B. licheniformis*, such as
the commercially available subtilisins Maxatase®
supplied by Gist-Brocades NV, Delft, Holland, and
Alcalase®, supplied by NOVO Industri A/S Copenhagen,
Denmark. Particularly suitable are proteases obtained
10 from a strain of *Bacillus* having maximum activity
throughout the pH range of 8-12, being commercially
available from NOVO Industri A/S under the Trade names
of Esperase® and Savinase®. The preparation of these
and analogues enzymes is described in GB Patent No.
15 1,243,784. These enzymes are generally presented as
granules, e.g. marumes, prills, T-granulates etc., and
may have enzyme activities of from 500 to 1700 Glycine
Units/mg. The proteolytic enzyme activity can be
determined by the method as described by M.L. Anson in
20 "Journal of General Physiology" Vol. 22 (1938), page 79
(one Anson unit/gram = 733 Glycine Units/milligram).

In the compositions of the invention proteolytic
enzymes may be present in amounts such that the final
25 composition has proteolytic enzyme activity of from
about 10^6 to 10^8 Glycine Units/Kilogram.

Other enzymes, such as lipolytic enzymes may also be
incorporated to improve fat removal. Typical examples
30 of commercial lipolytic enzymes are Lipase YL, Amano
CE, Wallerstein AW, Lipase My, and Lipolase ex Novo
Ind.

Testsi) Spot Test

5 The following powdered machine dishwashing composition were prepared:

	<u>Composition</u>	<u>Parts by Weight</u>
10	Sodium citrate 2 aq.	42
	Sodium disilicate ⁴⁾	35
	Sodium perborate monohydrate	8.4
	Sokalan CP ¹⁾	5
	TAED ²⁾ (83%)	5
15	Amylase	1.7
	Protease	1.7
	Adsorbing material ³⁾	1.2

20 1) = acrylic acid/maleic acid copolymer ex BASF

2) = N, N, N¹, N¹-tetraacetylethylene diamine bleach activator

25 3) = a) Laponite XLG ex Laporte Industries Ltd
b) Synthetic hydrotalcite, [Mg₆Al₂(OH)₁₆]CO₃.4H₂O obtainable from Joseph Crosfield and Sons - Warrington - U.K. under the tradename Macrosorb CT100

30 4) Obtainable from Joseph Crosfield and Sons - Warrington - U.K. under the tradename Pyramid G82.

10

Machine dishwashing experiments were carried out with the above formulations (a) and (b) at a product dosage of 17 g. per run (= 3.4 g/l) in a Bosch S 510 machine at a water intake of 5 litre (16°FH). The wash programme consisted of a pre-wash, main wash at 55°C, two intermediate rinses and a final rinse of 65°C.

5 Total washing time 65 minutes. The load per wash consisted of a dummy load together with five milk-glasses and two glass-plates. As in glass appearance terms egg yolk is notoriously known as problem-soil, it is used here as the standard-soil. The machine

10 dishwashing product and egg-yolk soiling (a dispersion of 2g egg yolk in ca. 20 ml water) were added to the wash-liquor at the start of the main wash cycle.

15

The glass-appearance was judged in terms of spot-score according to the following table.

20

Spot - score	Number of spots	
1	none	
2	1 - 5	
3	6 - 10	
25	4	11 - 20
5	21 - 30	
6	31 - 40	
7	41 - 50	
8	51 - 75	
30	9	76 - 100
10	101 - 150	
11	> 150	

35

GENERAL DESCRIPTION OF THE INVENTION

It has now surprisingly been found that the above goals can be achieved by the incorporation in a machine dishwashing composition of an effective level of a co-granule of an hydroxylated-like material, preferably a Zn/Al or Mg/Al hydroxylated, and a soluble alkali metal silicate.

It is therefore a first object of the present invention to provide a co-granule of an hydroxylated-like material, preferably a Zn/Al or Mg/Al hydroxylated, and an alkali metal silicate.

A co-granule of an alkali metal silicate which is soluble under machine dish wash conditions and hydroxylated-like material can be prepared by a process involving mixing the alkali metal silicate, which may be in the solution, powder or granular form and the hydroxylated-like material, which may be introduced as a dry powder or as a slurry in water or alkali metal silicate solution. This mixing takes place either in, or is followed by introduction into, suitable granulation equipment (e.g spray drier, roller compactor, fluid bed drier, marumeriser, pan granulator, extruder, tabletting machinery or any other suitable equipment). Water or alkali metal silicate solution may optionally be added to assist the granulation step (or as part of the formulation) and a post-granulation drying step may be needed to produce a free-flowing powder.

It is preferred, though not essential, that there is contact between the hydroxylated-like material and the alkali metal silicate in an aqueous phase at some time during the granulation step.

Preferably the weight ratio of alkali metal silicate to hydrotalcite-like material in the cogranule is within the range 500:1 to 1:50.

5 It is also a second object of the present invention to provide a machine dishwashing composition comprising a builder or builder mixture, buffering and/or alkaline agent, wherein it further comprises an effective amount of a co-granule of an alkali metal silicate and a hydrotalcite-like
10 material.

15 The effective level of the co-granule of alkali metal silicate and hydrotalcite-like material to be included in the machine dishwashing composition of the invention will be such to give a hydrotalcite-like material content which will range from about 0.01 to 40% by weight, usually from 0.1 to 20% by weight, preferably from 0.5 to 10% and most preferably from 0.5 - 5% by weight.

20 The machine dishwashing composition of the invention will normally also contain a builder or builder mixture, buffering and/or alkaline agents, optionally but preferably also a bleaching agent and an enzyme or mixtures of enzymes.

25 The machine dishwashing compositions of the present invention can be manufactured and presented in any physical form such as a powder, liquid, paste or solid blocks or tablets, and are preferably formulated such that they provide a wash liquor with a pH of between 6 and 13, preferably from 8-11, and more preferably from 9.5-10.5
30 (measured at a concentration of from 0.1-0.3% by weight in water).

SPECIFIC DESCRIPTION OF THE INVENTION

5 The invention will now be illustrated by way of the following examples (percentages are by weight unless otherwise stated).

EXAMPLE 1 - COMPARATIVE EXAMPLE

10 A first spot test was realised as described herein before wherein the absorbent was Laponite XLG ex Laporte Industries Ltd. Laponite XLG and TAED were added as cocranules to the washing composition.

15 The Spot Score was 6.

EXAMPLE 2

20 A second spot test was realised as described herein before wherein the absorbent was $[\text{Mg}_6\text{Al}_2(\text{OH})_{16}]\text{CO}_3 \cdot 4\text{H}_2\text{O}$ obtainable from Joseph Crosfield & Sons - Warrington - U.K. under the trade name Macrosorb CT100.

25 Disilicate and hydrotalcite material were added as cocranules to the washing composition.

The cocranules were produced as follows.

30 2.5 kg of granular sodium disilicate (Pyramid G82 ex-Crosfield) were mixed with 88.2g Macrosorb CT100 (ex-Crosfield) for 3 min in a Lodige plough shear mixer. 400g of a 10% sodium disilicate solution (diluted Crystal 120 ex-Crosfield), heated to 80C, were sprayed onto this mixture using a Delevan nozzle sprayer. Mixing continued for 5 min. The granulated product was then dried in a fluidised bed at 80°C until the total water content was

23-24% by weight. The 200-1000 micron fraction was sieved out and used in a dishwashing composition as above described.

5 The Spot Score was 9.

EXAMPLE 3

10 A third spot test was realised as described herein before wherein the absorbent was $[\text{Mg}_6\text{Al}_2(\text{OH})_{16}]\text{CO}_3 \cdot 4\text{H}_2\text{O}$ obtainable from Joseph Crosfield & Sons under the trade name Macrosorb CT100.

15 Disilicate and hydrotalcite material were added as cogranules to the washing composition.

The cogranules were produced as follows:

20 2.5 kg of granular sodium disilicate (as in Example 2) were placed in the Lodige mixer. 88.2 g Macrosorb CT100 were mixed with 400g of a 10% sodium disilicate solution using an ultra turrax system then sprayed onto the granular disilicate. Granulation, drying and sieving were done as in Example 2.

25 The Spot Score was 6.


Comparing Examples 2 and 3 with Example 1, it can be seen that a cogranule of soluble alkali metal silicate and 30 hydrotalcite-like material constitutes a good alternative to synthetic hectorites.

Comparing Example 2 with Example 3, it can be seen that depending on the manufacturing process of the cogranules, 35 the performance of the end-product can be slightly

different. Without wishing to be bound by any theory, it can be assumed that the hydrotalcite like material reacts with the soluble alkali metal silicate in solution to form a complex which could bind proteinaceous species. If this 5 theory is correct, it can be assumed that Example 3 was made via a process which should give controlled and better complexation between the hydrotalcite-like material and the alkali metal silicate.

CLAIMS

1. Cogranule of an hydrotalcite like material and alkali metal silicate, the hydrotalcite-like material being a product having the following composition:



10 where:

M is any 1+ or 2+ cation or combination thereof

N is any 3+ or 4+ cation or combination thereof

k is the sum of the individual mole fractions of
15 the 1+ cations

m is the sum of the individual mole fractions of
the 2+ cations

n is the sum of the individual mole fractions of
the 3+ cations

20 p is the sum of the individual mole fractions of
the 4+ cations

where either but not both of k and m or n and p
can be zero and $k+m+n+p=1$.

25 A_z^{y-} being any anion of charge $y-$ and mole fraction
z, or combination of anions of similar or
differing $y-$ and $k+2m+3n+4p-2-zy=0$ and x can range
from 1 to 100.

30 2. Cogranule according to claim 1 wherein the ratio of
alkali metal silicate to hydrotalcite-like material is
within the range 500:1 to 1:50.

35 3. Machine dishwashing composition comprising a builder or
builder mixture, buffering and/or alkaline agent,

wherein it further comprises an effective amount of a cogranule of alkali metal silicate and a hydrotalcite-like material according to claim 1 or 2.

INTERNATIONAL SEARCH REPORT

PCT/EP 95/00102

A. CLASSIFICATION OF SUBJECT MATTER
C 11 D 3/02, C 11 D 17/00

According to International Patent Classification (IPC) or to both national classification and IPC 6

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C 11 D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO, A, 89/08 693 (THE DOW CHEMICAL CO.) 21 September 1989 (21.09.89), page 3, lines 16-34; page 6, line 20 - page 7, line 12; example 5; claims. --	1-3
X	DE, A, 4 122 200 (HENKEL) 07 January 1993 (07.01.93), the whole document. --	1-3
P, X	WO, A, 94/03 574 (UNILEVER) 17 February 1994 (17.02.94), page 3, line 18 - page 7, line 29; examples; claims 1-6. -----	1-3

 Further documents are listed in the continuation of box C. Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search
30 March 1995

Date of mailing of the international search report

03.05.95

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016Authorized officer
SEIRAFI e.h.

ANHANG

zum internationalen Recherchenbericht über die internationale Patentanmeldung Nr.

ANNEX

to the International Search Report to the International Patent Application No.

ANNEXE

au rapport de recherche international relatif à la demande de brevet international n°

PCT/EP 95/00102 SAE 103246

In diesem Anhang sind die Mitglieder der Patentfamilien der in oben genannten internationalen Recherchenbericht angeführten Patentdokumente angegeben. Diese Angaben dienen nur zur Orientierung und erfolgen ohne Gewähr.

This Annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The Office is in no way liable for these particulars which are given merely for the purpose of information.

La présente annexe indique les membres de la famille de brevets relatifs aux documents de brevets cités dans le rapport de recherche international visé ci-dessus. Les renseignements fournis sont donnés à titre indicatif et n'engagent pas la responsabilité de l'Office.

Im Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication	
WO A1 8908693	21-09-89	US A 5015409 CA A1 1314192 EP A1 364543 EP A4 364543 JP T2 2503688 JP B4 6062930 US A 5232627 AT E 93815 AU A1 59754/86 AU B2 595214 BR A 8603134 CN A 86104606 CN B 1016352 CN A 1063266 DE CO 3688954 DE T2 3688954 DK A0 3203/86 DK A 3203/86 EP A2 207811 EP A3 207811 EP B1 207811 ES AF 2000647 IL A0 79304 IL A1 79304 JP A2 62036007 KR B1 9004487 NO A0 862726 NO A 862726 ZA A 8604992 US A 4990268 US A 5154932 AT E 93213 AU A1 59756/86 AU B2 580432 BR A 8603135 CA A1 1264926 CN A 86104614 CN B 1006801 DE CO 3688896 DE T2 3688896 DK A0 3204/86 DK A 3204/86 EP A2 207810 EP A3 207810 EP B1 207810 ES AF 2000457 IL A0 79303 IL A1 79303 IN A 167449 JP A2 62036481 JP B4 6099679 KR B1 9402568 NO A0 862725 NO A 862725 NO B 175598 NO C 175598 US A 4664843 ZA A 8604991 US A 4790954 US A 5196143 US A 5308547 US A 5094778	14-05-91 09-03-93 25-04-90 05-09-90 01-11-90 17-08-94 03-08-93 15-09-93 22-01-87 29-03-90 24-02-87 04-02-87 22-04-92 05-08-92 07-10-93 23-12-93 04-07-86 06-01-87 07-01-87 17-11-88 01-09-93 16-03-88 31-10-86 12-07-90 17-02-87 28-06-90 04-07-86 06-01-87 30-03-88 05-02-91 13-10-92 15-09-93 22-01-87 12-01-89 24-02-87 30-01-90 22-04-87 14-02-90 23-09-93 09-12-93 04-07-86 06-01-87 07-01-87 17-11-88 18-08-93 01-03-88 31-10-86 09-02-90 27-10-90 17-02-87 07-12-94 25-03-94 04-07-86 06-01-87 25-07-94 02-11-94 12-05-87 30-03-88 13-12-88 23-03-93 03-05-94 10-03-92	14-05-91 09-03-93 25-04-90 05-09-90 01-11-90 17-08-94 03-08-93 15-09-93 22-01-87 29-03-90 24-02-87 04-02-87 22-04-92 05-08-92 07-10-93 23-12-93 04-07-86 06-01-87 07-01-87 17-11-88 01-09-93 16-03-88 31-10-86 12-07-90 17-02-87 28-06-90 04-07-86 06-01-87 30-03-88 05-02-91 13-10-92 15-09-93 22-01-87 12-01-89 24-02-87 30-01-90 22-04-87 14-02-90 23-09-93 09-12-93 04-07-86 06-01-87 07-01-87 17-11-88 18-08-93 01-03-88 31-10-86 09-02-90 27-10-90 17-02-87 07-12-94 25-03-94 04-07-86 06-01-87 25-07-94 02-11-94 12-05-87 30-03-88 13-12-88 23-03-93 03-05-94 10-03-92
DE A1 4122200	07-01-93	MX A1 9203932	02-03-93	

WO A1 930126 21-01-93

WO A1 9403574

17-02-94

keine - none - rien

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- BLACK BORDERS**
- IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- FADED TEXT OR DRAWING**
- BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- SKEWED/SLANTED IMAGES**
- COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- GRAY SCALE DOCUMENTS**
- LINES OR MARKS ON ORIGINAL DOCUMENT**
- REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.